

USES

- Grouting of voids, Honey combs, tiles. This is a gelling agent added to fast setting cement slurry compiling water and cement
- Can be used for against running water and works excellent then if followed by Protekta Protonex (SS)

DESCRIPTION

Sometimes there is a setting problem of cement or clay like Protekta Protonex SB in the presence of fast running water present in the void. This catalyst can be used even as such without any filler for providing a method of placing and setting the grouting material in a void containing water or where there is a fast running water and even in other cases.

This is a specific formulation and suitable for all sorts of portland cement, pozzolanic materials, Protekta Protonex SB, fly ash. These compositions are normally delivered to the voids by usual grouting machine.

Sometimes the void or the damaged area need water type product which can be grouted and which interacts with the concrete or building material immediately. In such cases Protekta MS can be injected in pure form without any filler, in order of merit.

IMPORTANT NOTE

Protekta products are non-hazardous when properly handled, stored and applied. When handling suitable protective clothing should be worn. The materials should not be ingested, inhaled or make skin contact. MSDS are available.

WARRANTY:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge and should be used only as a guide. Tech Dry (India) Pvt Ltd reserves the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. The information in this document is based on the present state of our knowledge and is applicable to the product. Tech Dry (India) Pvt Ltd is responsible for the quality of the product at the time of despatch but is not responsible for its quality after subsequent storage, handling and application. Neither Tech Dry (India) Pvt Ltd nor its associated companies shall be held liable for any damage resulting from the handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

APPLICATION

Can be used as a clear liquid or in combination with cement or SB or followed by SS. Grout by machine under pressure

NOTE: Catalyst C and S have identical function however C is the fastest and S is the medium setting agent.

TECHNICAL DATA

Colour : Clear Liquid
pH Value : 6 - 7
Specific Gravity : 1.05 g/cm³

COVERAGE: Depends on the surface

SHELF LIFE: 6 months in a closed uncontaminated container and should be used before the use-by-date printed on the container. However if the product is passed its used-by-date it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice

STORAGE: To be stored in closed containers in a cool place and prevent from extremes of heat

HEALTH & SAFETY: Non-Hazardous, Non-toxic, Non-flammable

Tech-Dry (India) Pvt. Ltd.

769, Ground Floor, I Cross, I Stage, Indiranagar, Bangalore 560 0328, Ph: ++91-80-25255294 / 25255406,
Fax: ++91-80-25289159. E.mail: techdry@airtelbroadband.in, Website: www.techdryindia.com