

USES

- Can be applied directly to the concrete
- Excellent for damp proofing basements
- Excellent for leaking bricks and concrete walls

PROPERTIES

- Excellent adhesion
- Breathable
- Provides a tough and durable coating.
- Has excellent weather resistance properties and is suitable for exterior applications.
- Seals the concrete walls effectively and bridges the shrinkage cracks

DESCRIPTION

Protekta Doug Bond is one of the latest developments by our laboratory in the field of Polymer Modified Cementitious coating.

Protekta Doug Bond provides a waterproofing coating suitable for reservoirs, water tanks, roofs etc.

APPLICATION

Protekta Doug Bond is one component polymer which is to be mixed with 2 parts cement + 3 parts

Silica Sand + 1 part Calcium Carbonate + 0.1 part Lime to prepare slurry.

TECHNICAL DATA

- Mixed Density : 1.058
- Colour : White
- Toxicity : Non toxic
- Adhesion to concrete : excellent

DOSAGE: To be used according to the workability required.

SHELF LIFE : 6 months in a closed uncontaminated container and should be used before the use-by-date printed on the container. However if the product is passed its used-by-date it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice

STORAGE: To be stored in closed containers in a cool place and prevent from extremes of heat

HEALTH & SAFETY: Non-Hazardous, Non-toxic, Non-flammable

IMPORTANT NOTE

Protekta products are non-hazardous when properly handled, stored and applied. When handling suitable protective clothing should be worn. The materials should not be ingested, inhaled or make skin contact. MSDS are available.

WARRANTY:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge and should be used only as a guide. Tech Dry (India) Pvt Ltd reserves the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. The information in this document is based on the present state of our knowledge and is applicable to the product. Tech Dry (India) Pvt Ltd is responsible for the quality of the product at the time of despatch but is not responsible for its quality after subsequent storage, handling and application. Neither Tech Dry (India) Pvt Ltd nor its associated companies shall be held liable for any damage resulting from the handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Tech-Dry (India) Pvt. Ltd.

769, Ground Floor, I Cross, I Stage, Indiranagar, Bangalore 560 0328, Ph: ++91-80-25255294 / 25255406,
Fax: ++91-80-25289159. E.mail: techdry@airtelbroadband.in, Website: www.techdryindia.com