

Water based Solvent free

USES

It can be use as final hard coating on Floor, roofs, basements and other concrete surface.

PROPERTIES

- Flexibility
- Bonding
- Superior adhesiveness
- Resistance to movement of the supports
- Resistance to punctures
- Resistance to stress induced by temperature variations
- Resistance to wind effects
- Does not block pores and capillaries and allows normal breathing of the building
- Weather resistant.
- Highly durable in all Climatic Conditions.
- Acts as a Protective barrier against ingress for concrete/steel structures.
- Accommodates continuous and pronounced cycle movement.

APPLICATION

- One component, ready to use, simple to apply
- Can be applied by using brush

DESCRIPTION

This is a special abrasion free hard coat produced by using co-polymers including Protekta -500 and the method involved. An aqueous emulsion to control stability of bitumen type emulsion containing an effective amount of cationic emulsifying agents.

COVERAGE: 15-20 sq. ft. per ltr

SHELF LIFE: 6 months in a closed uncontaminated container and should be used before the use-by-date printed on the container. However if the product is passed its used-by-date it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice

STORAGE: To be stored in closed containers in a cool place and prevent from extremes of heat

HEALTH & SAFETY: Non-Hazardous, Non-toxic, Non-flammable

IMPORTANT NOTE

Protekta products are non-hazardous when properly handled, stored and applied. When handling suitable protective clothing should be worn. The materials should not be ingested, inhaled or make skin contact. MSDS are available.

WARRANTY:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge and should be used only as a guide. Tech Dry (India) Pvt Ltd reserves the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. The information in this document is based on the present state of our knowledge and is applicable to the product. Tech Dry (India) Pvt Ltd is responsible for the quality of the product at the time of despatch but is not responsible for its quality after subsequent storage, handling and application. Neither Tech Dry (India) Pvt Ltd nor its associated companies shall be held liable for any damage resulting from the handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Tech-Dry (India) Pvt. Ltd.

769, Ground Floor, I Cross, I Stage, Indiranagar, Bangalore 560 0328, Ph: ++91-80-25255294 / 25255406,
Fax: ++91-80-25289159. E.mail: techdry@airtelbroadband.in, Website: www.techdryindia.com