

PROTEKTA G

USES

- Waterproofing of leaky concrete roof slabs
- Waterproofing of earth, mud brick and cement block walls.
- Waterproofing of external brick walls.
- Waterproofing of A.C. sheet or tiled roof.
- To provide damp-proof course in new buildings, in sandstone walls and pavings, in terracotta and ceramic pavements
- To prevent surface staining from waterborne pollution, algae, moss, mould etc
- Since Protekta G is water based it is totally harmless.
- Offers permanent waterproof protection
- Easy to apply
- Surface appearance is unchanged
- Porosity and vapour permeability are unaffected
- Can be painted after treatment

DESCRIPTION

As a damp-proof course (just above the existing damp-roof course) in buildings where the existing damp proof course is not functioning.

APPLICATION

- Clean the surface
- Test for Clean the surface
- Test for cracks and other faults
- Spray Protekta Base on dry surface

Important Note

Protekta products are non-hazardous when properly handled, stored and applied. When handling suitable protective clothing should be worn. The materials should not be ingested, inhaled or make skin contact. MSDS can be provided.

Warranty

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge and should be used only as a guide. Tech Dry (India) Pvt Ltd reserves the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. The information in this document is based on the present state of our knowledge and is applicable to the product. It does not represent a guarantee of the properties of the product. Tech Dry (India) Pvt Ltd is responsible for the quality of the product at the time of despatch but is not responsible for its quality after subsequent storage, handling and application. Neither Tech Dry (India) Pvt Ltd nor its associated companies shall be held liable for any damage resulting from the handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

- Fill cracks and joints with Protekta Sealant treated mortar
- Spray Protekta G
- The liquid is sprayed evenly under low pressure over the entire area to be waterproofed. Two applications are given. Particular care should be taken to see that vertical surfaces are evenly wetted.

TECHNICAL DATA

Appearance	: Clear aqueous solution
pH	: 12
Density	: 1.13
Viscosity	: Similar to water
Flash point	: >100%

COVERAGE : 30-40 sq.ft

SHELF LIFE

6 months in a closed uncontaminated container and should be used before the use-by-date printed on the container. However if the product is passed its used-by-date it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice

STORAGE : To be stored in closed containers in a cool place and prevent from extremes of heat

HEALTH & SAFETY : Non-Hazardous, Non-toxic, Non-flammable

TECH-DRY (INDIA) PVT. LTD.
BUILDING PROTECTION SYSTEMS
769, Ground Floor, I Cross, I Stage, Indiranagar, Bangalore -560038
Tel: (080) 25255294 / 25255406 Fax: (080) 25289159
E.mail: techdry@touchtelindia.net