

PROTEKTA KP

USES

Protekta KP is an excellent product for both terraces and walls.

PROPERTIES

- Waterproofing
- Thermal Insulation
- Seals hairline cracks

DESCRIPTION

This is a magic product, which is supplied in the form of solid powder and can be mixed with water to obtain workable mortar. If this product is applied over the walls or any other masonry surface it imparts waterproofing, seals hairline cracks if any and gives Thermal Insulation to the building. Any pigment can be added to this composition to provide colour of your choice.

APPLICATION

Brush coat 3-4mm in several thin layers.

TECHNICAL DATA

Appearance : White powder
Thermal conductivity: 0.032

COVERAGE: Depends on surface and thickness

SHELF LIFE: 6 months in a closed uncontaminated container and should be used before the use-by-date printed on the container. However if the product is passed its used-by-date it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice

STORAGE: To be stored in closed containers in a cool place and prevent from extremes of heat

HEALTH & SAFETY: Non-Hazardous, Non-toxic, Non-flammable

Protekta products are non-hazardous when properly handled, stored and applied. When handling suitable protective clothing should be worn. The materials should not be ingested, inhaled or make skin contact. MSDS can be provided.

Warranty

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge and should be used only as a guide. Tech Dry (India) Pvt Ltd reserves the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. The information in this document is based on the present state of our knowledge and is applicable to the product. It does not represent a guarantee of the properties of the product. Tech Dry (India) Pvt Ltd is responsible for the quality of the product at the time of despatch but is not responsible for its quality after subsequent storage, handling and application. Neither Tech Dry (India) Pvt Ltd nor its associated companies shall be held liable for any damage resulting from the handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

TECH-DRY (INDIA) PVT. LTD.

BUILDING PROTECTION SYSTEMS

769, Ground Floor, I Cross, I Stage, Indiranagar, Bangalore -560038

Tel: (080) 25255294 / 25255406 Fax: (080) 25289159

E.mail: techdry@touchtelindia.net