

USES

- It is specially made for bonding glass to metal and also for other substrates.
- Outstanding weatherability and resistance to UV degradation
- High gloss, hardness and adhesion to various substrates like Metals, Glass, Plastics, wood, concrete
- Excellent resistance to water, alcohols, oils, solvent, chemical fumes, dilute acids, alkalies.

DESCRIPTION

Protekta Fix is a co-polymer of various Acrylic Monomers. Multipurpose adhesive based on acrylic polymers. Medium viscosity, which dries to transparent film.

APPLICATION

Must be applied on both the surface (say glass and metal)
Gently press them and leave them over night although bonding would start much sooner.

TECHNICAL DATA

Solid Content	: 46± 1%
Viscosity at 30°C	: 5 —10 poise
Acid Value	: Neutral
Properties of Film	: Tough

COVERAGE: 10 sq. ft per kg

SHELF LIFE: 6 months in a closed uncontaminated container and should be used before the use-by-date printed on the container. However if the product is passed its used-by-date it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice

STORAGE: To be stored in closed containers in a cool place and prevent from extremes of heat

HEALTH & SAFETY: Non-Hazardous, Non-toxic, Non-flammable

IMPORTANT NOTE

Protekta products are non-hazardous when properly handled, stored and applied. When handling suitable protective clothing should be worn. The materials should not be ingested, inhaled or make skin contact. MSDS are available.

WARRANTY:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge and should be used only as a guide. Tech Dry (India) Pvt Ltd reserves the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. The information in this document is based on the present state of our knowledge and is applicable to the product. Tech Dry (India) Pvt Ltd is responsible for the quality of the product at the time of despatch but is not responsible for its quality after subsequent storage, handling and application. Neither Tech Dry (India) Pvt Ltd nor its associated companies shall be held liable for any damage resulting from the handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

Tech-Dry (India) Pvt. Ltd.

769, Ground Floor, I Cross, I Stage, Indiranagar, Bangalore 560 0328, Ph: ++91-80-25255294 / 25255406,
Fax: ++91-80-25289159. E.mail: techdry@airtelbroadband.in, Website: www.techdryindia.com