

DESCRIPTION

Protekta Tile-N-Fix is ready to use cement and special chemicals based non-shrink, self-curing, waterproof, excellent tile adhesive for fixing ceramic and mosaic tiles on horizontal and vertical surface.

ADVANTAGES

- Waterproof
- Ready to use
- Good bonding compared to conventional cement mortar
- Good mechanical strength
- Curing is not required

USES

Surface should be cleaned to remove all loosely adhering particles, oil, grease etc. Pre-wetting of substrate is essential. Tiles shall be cleaned of dust with brush/cloth but shall be DRY while using. Apply the paste on prepared surface with 3 mm approx thickness and comb the surface with notched trowel. Place tiles within 15 minutes of mixing and press firmly with twisting movements. Uneven surface may require more than 3 mm thickness, use damp cloth to remove excess paste from tie surface. Tile joints may be filled by Protekta Tile-N-Grout.

IMPORTANT NOTE

Protekta products are non-hazardous when properly handled, stored and applied. When handling suitable protective clothing should be worn. The materials should not be ingested, inhaled or make skin contact. MSDS are available.

WARRANTY:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge and should be used only as a guide. Tech Dry (India) Pvt Ltd reserves the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. The information in this document is based on the present state of our knowledge and is applicable to the product. Tech Dry (India) Pvt Ltd is responsible for the quality of the product at the time of despatch but is not responsible for its quality after subsequent storage, handling and application. Neither Tech Dry (India) Pvt Ltd nor its associated companies shall be held liable for any damage resulting from the handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale.

COVERAGE: 2.0 to 2.5 kg per sq. mtr. / 3mm. thickness (Depends upon surface)

STORAGE: Keep in a dry place, avoid moisture ingress.

SHELF LIFE: 6 months in a closed uncontaminated container and should be used before the use-by-date printed on the container. However if the product is passed its used-by-date it is not necessarily unusable. A quality control should be performed on the properties relevant to the application or otherwise contact the manufacturer for further advice

STORAGE: To be stored in closed containers in a cool place and prevent from extremes of heat

HEALTH & SAFETY: Non-Hazardous, Non-toxic, Non-flammable

CAUTION

Add powder to water, Prepare only required quantity to utilize within 15 minutes. Avoid fixing tiles outdoor when rain is imminent, correct ratio of Protekta Tile-N-Fix and water is essential for optimum performance.

Tech-Dry (India) Pvt. Ltd.

769, Ground Floor, I Cross, I Stage, Indiranagar, Bangalore 560 0328, Ph: ++91-80-25255294 / 25255406,
Fax: ++91-80-25289159. E.mail: techdry@airtelbroadband.in, Website: www.techdryindia.com